

SB20150LCT

DUAL LOW VF SCHOTTKY RECTIFIER

VOLTAGE 150 Volts **CURRENT** 20 Amperes

FEATURES

- Low forward voltage drop, low power losses
- High efficiency operation
- In compliance with EU RoHS 2002/95/EC directives


MECHANICAL DATA

Case : TO-220AB, Plastic

Terminals : Solderable per MIL-STD-750, Method 2026

Weight: 0.0655 ounces, 1.859 grams.

Unit: inch (mm)



MAXIMUM RATINGS($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	150	V
Maximum average forward rectified current (Fig.3)	$I_{F(AV)}$	20 10	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load per diode	I_{FSM}	200	A
Typical thermal resistance	$R_{\theta JC}$	2.5	$^{\circ}\text{C/W}$
Operating junction	T_J	-55 to + 150	$^{\circ}\text{C}$
Storage temperature range	T_{STG}	-55 to + 150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Breakdown voltage per diode	V_{BR}	$I_R=1.0\text{mA}$	103	120	-	V
Instantaneous forward voltage per diode ⁽¹⁾	V_F	$I_F=5\text{A}$	-	0.57	0.62	V
		$I_F=10\text{A}$	-	-	0.77	V
		$I_F=5\text{A}$	-	0.54	-	V
		$I_F=10\text{A}$	-	0.64	0.72	V
Reverse current per diode ⁽²⁾	I_R	$V_R=70\text{V}$	-	12	40	μA
		$V_R=100\text{V}$	-	-	500	μA
		$T_J=25^{\circ}\text{C}$	-	-	35	μA
		$T_J=125^{\circ}\text{C}$	-	-	-	mA

Note.1 Pulse test : 380 μs pulse width, 1% duty cycle

2. Pulse test : Pulse width $\leq 2.5\text{ms}$

SB20150LCT




Fig.1 Typical Forward Characteristics




Fig.2 Typical Reverse Characteristics




Fig.3 Forward Current Derating Curve




Fig.4 Typical Junction Capacitance